



AURA STEPLIGHT S

IP65 IK08    | TIPOLOGIA | *TYPOLGY*Segnapasso | *Steplight*POSIZIONE INSTALLATIVA | *INSTALLATION POSITION*A parete | *Wall*AMBIENTE INSTALLATIVO | *INSTALLATION LOCATION*Esterno | *Outdoor*

AURA STEPLIGHT S

4,5W Finish .01
kg 0,2 Finish .06 .10
kg 0,25 81mm

AURA STEPLIGHT S

CARATTERISTICHE ELETTRICHE | ELECTRICAL FEATURES

POTENZA ASSORBITA POWER CONSUMPTION	4,5W
ALIMENTAZIONE POWER SUPPLY	24Vdc
ALIMENTATORE POWER SUPPLY UNIT	24Vdc non incluso not included
COLLEGAMENTO CONNECTION	Parallelo Parallel

CARATTERISTICHE ILLUMINOTECNICHE | LIGHTING FEATURES

COLORE LED LED COLOUR	2200K, 2700K, 3000K, 4000K, Red, Green, Blue
INDICE RESA CROMATICA CRI CRI	>80
BINNING	3 step MacAdam 3 MacAdam steps
OTTICHE OPTICS	ASYM
FLUSSO REALE EMESSO - 3000K REAL OUTPUT FLUX	4,5W 58lm
DURATA MEDIA LED AVERAGE LED LIFE	50.000h L80 B10

CARATTERISTICHE MECCANICHE | MECHANICAL FEATURES

PESO WEIGHT	Finishig .01 Finishig .06 .10	Kg 0,2 Kg 0,25
FINITURE FINISHES	Alluminio anodizzato, Bianco txt, Acciaio, Nero txt, Corten, Acciaio spazzolato, Antracite txt, Sans, Bronzo anodico opaco Anodized aluminium, txt White, Steel, txt Black, Corten, txt Anthracite, Sand, Anodic bronze matt	
INSTALLAZIONE INSTALLATION	A incasso su cartongesso o legno con molla (non inclusa) A parete su muratura per interferenza tramite o-ring (incluso) e cassaforma (non inclusa). Recessed on plasterboard or wood with spring (not included) Wall-mounted on masonry via interference fit with O-rings (included) and housing box (not included).	
MATERIALE MATERIAL	Corpo in alluminio anticorodal, Ghiera in alluminio anticorodal (versione alluminio), Ghiera in acciaio inox AISI 316L (versione inox), Vetro temperato Anticorodal aluminium body, Anticorodal aluminium trim (aluminium version), AISI 316L stainless steel trim (inox version), Tempered glass	


CARATTERISTICHE GENERALI | GENERAL FEATURES

TEMPERATURA DI ESERCIZIO OPERATING TEMPERATURE	-10°C +45°C
GRADO DI PROTEZIONE INGRESS PROTECTION	IP65
GRADO DI RESISTENZA IMPACT RESISTANCE	IK08
GLOW WIRE TEST GLOW WIRE TEST	960°C
TEMPERATURA SCHERMO SCREEN TEMPERATURE	40° @ Ta = 25°
CLASSE DI ISOLAMENTO APPLIANCE CLASS	III
CALPESTABILE WALKOVER	/
CARRABILE DRIVE OVER	/
SICUREZZA STANDARD STANDARD SAFETY	/


AURA STEPLIGHT S

ACCESSORI | ACCESSORIES


CODICE / CODE	ML032
TIPOLOGIA / TYPOLOGY	Molla di torsione <i>Torsion spring</i>  kg 0,001
MATERIALE / MATERIAL	Acciaio armonico <i>Harmonic steel</i>



CODICE / CODE	CAW32
TIPOLOGIA / TYPOLOGY	Cassaforma <i>Housing box</i>  kg 0,09
MATERIALE / MATERIAL	PVC



CODICE / CODE	CAI32
TIPOLOGIA / TYPOLOGY	Cassaforma <i>Housing box</i>  kg 0,06
MATERIALE / MATERIAL	ABS



a scelta | to be chosen