



NEIS IP65 S 230V_{ac}IP65 IK06 CE   TIPOLOGIA | *TYPOLGY*Segnapasso | *Steplight*POSIZIONE INSTALLATIVA | *INSTALLATION POSITION*A parete | *Wall*AMBIENTE INSTALLATIVO | *INSTALLATION LOCATION*Esterno | *Outdoor*

CASSANDRA S

4W

 kg 0,4

NEIS IP65 S 230Vac

CARATTERISTICHE ELETTRICHE | ELECTRICAL FEATURES

POTENZA ASSORBITA POWER CONSUMPTION	4W
ALIMENTAZIONE POWER SUPPLY	230Vac
FREQUENZA FREQUENCY	50/60Hz
ALIMENTATORE POWER SUPPLY UNIT	Incluso Included
COLLEGAMENTO CONNECTION	Tensione di rete Mains voltage

CARATTERISTICHE ILLUMINOTECNICHE | LIGHTING FEATURES

COLORE LED LED COLOUR	2700K, 3000K, 4000K
INDICE RESA CROMATICA CRI CRI	>80
BINNING	3 step MacAdam 3 MacAdam steps
OTTICHE OPTICS	Diffused
FLUSSO REALE EMESSE - 3000K REAL OUTPUT FLUX	4W 145lm
DURATA MEDIA LED AVERAGE LED LIFE	50.000h L80 B10

CARATTERISTICHE MECCANICHE | MECHANICAL FEATURES

PESO WEIGHT	kg 0,25
FINITURE FINISHES	Bianco txt, Grigio txt, Nero txt, Corten, Antracite txt, Sand txt White, txt Grey, txt Black, Corten, txt Anthracite, Sand
INSTALLAZIONE INSTALLATION	A parete su muratura, legno o cappotto con viti (non incluse) A incasso su muratura con cassaforma (non inclusa) e viti (non incluse) On brickwork, wood or external wall mounting with screws (not included) Recessed on brickwork with housing box (not included) and screws (not included)
MATERIALE MATERIAL	Corpo in alluminio anticorodal, Diffusore in PMMA opalino Anticorodal aluminium body, Opal PMMA diffuser

CARATTERISTICHE GENERALI | GENERAL FEATURES

TEMPERATURA DI ESERCIZIO OPERATING TEMPERATURE	-10°C +45°C
GRADO DI PROTEZIONE INGRESS PROTECTION	IP65
GRADO DI RESISTENZA IMPACT RESISTANCE	IK06
GLOW WIRE TEST GLOW WIRE TEST	960°C
TEMPERATURA SCHERMO SCREEN TEMPERATURE	40° @ Ta = 25°
CLASSE DI ISOLAMENTO APPLIANCE CLASS	I
CALPESTABILE WALKOVER	/
CARRABILE DRIVE OVER	/
SICUREZZA STANDARD STANDARD SAFETY	/
SICUREZZA FOTOBIOLOGICA PHOTOBIOLOGICAL SAFETY	GR1

NEIS IP65 S 230V_{ac}

ACCESSORI | ACCESSORIES

CODICE / CODE	CAS03
TIPOLOGIA / TYPOLOGY	Cassaforma Housing box
MATERIALE / MATERIAL	Polipropilene Polypropylene

 kg 0,04