

NEW RIVER XL1

IP68 IK09 CE III     | A > A+ > A++

TIPOLOGIA | TYPOLOGY


Incasso | Recessed

POSIZIONE INSTALLATIVA | INSTALLATION POSITION

A terra, a parete, a immersione | Floor or wall mounting and by immersion

AMBIENTE INSTALLATIVO | INSTALLATION LOCATION

Esterno | Outdoor



RIVER XL1

12W



kg 2,4



102 mm

NEW RIVER XL1

CARATTERISTICHE ELETTRICHE | ELECTRICAL FEATURES

POTENZA ASSORBITA POWER CONSUMPTION	12W
ALIMENTAZIONE POWER SUPPLY	24Vdc
ALIMENTATORE POWER SUPPLY UNIT	12W - 24Vdc (Non incluso Not included)
DIMMERAZIONE DIMMING	Dimmerabile Push, DMX, DALI, 1-10V, taglio di fase Push, DMX, DALI, 1-10V, phase cut dimmable
COLLEGAMENTO CONNECTION	Parallelo Parallel

CARATTERISTICHE ILLUMINOTECNICHE | LIGHTING FEATURES

COLORE LED LED COLOUR	Amber, 2200K, 2700K, 3000K, 4000K, Red, Green, Blue			
INDICE RESA CROMATICA CRI CRI	>80 (2200K, 2700K, 3000K, 4000K)			
OTTICHE OPTICS	18°, 24°, 36°, 60°, ASYM, 20°x50°			
FLUSSO TOTALE REALE TOTAL OUTPUT LUMENS	36°	680lm (2700K)	755lm (3000K)	831lm (4000K)
DURATA MEDIA LED AVERAGE LED LIFE	50.000h L80 B10			

CARATTERISTICHE MECCANICHE | MECHANICAL FEATURES


PESO WEIGHT	kg 2,4
FINITURE FINISHES	Acciaio Steel
INSTALLAZIONE INSTALLATION	A incasso a terra con cassaforma (non inclusa) e viti autofilettanti (incluse) Recessed on ground with housing box (not included) and screws (included)
MATERIALE MATERIAL	Corpo in acciaio inox AISI 316L, ghiera in acciaio Inox AISI 316L, vetro temperato trasparente AISI 316L stainless steel body, AISI 316L stainless trim, transparent tempered glass



CARATTERISTICHE GENERALI | GENERAL FEATURES


TEMPERATURA DI ESERCIZIO OPERATING TEMPERATURE	-10°C +45°C
GRADO DI PROTEZIONE INGRESS PROTECTION	IP68
GRADO DI RESISTENZA IMPACT RESISTANCE	IK09
GLOW WIRE TEST GLOW WIRE TEST	960°C
TEMPERATURA MASSIMA APPARECCHIO MAX. TEMPERATURE OF FIXTURE	40° @ Ta = 25°
CLASSE DI ISOLAMENTO APPLIANCE CLASS	III
CALPESTABILE WALKOVER	Sì / Yes
CARRABILE DRIVE OVER	Sì / Yes
CAVI DI ALIMENTAZIONE POWER CABLES	Fornito con 3 m di cavo Provided with 3 m cable
SICUREZZA STANDARD STANDARD SAFETY	WP System
SICUREZZA FOTOBIOLOGICA PHOTOBIOLOGICAL SAFETY	GR1

NEW RIVER XL1

ACCESSORI | ACCESSORIES

Standard	CODICE / CODE	CA101
	TIPOLOGIA / TYPOLOGY	Cassaforma Housing box  kg 0,33
	MATERIALE MATERIAL	Polietilene Polyethylene



IP68	CODICE / CODE	C8101
	TIPOLOGIA / TYPOLOGY	Cassaforma Housing box  kg 0,04
	MATERIALE MATERIAL	PVC

